



Iloform™ TDN 81

Neat forming oil

Description

Castrol Iloform™ TDN 81 is a medium viscosity, chlorinated, heavy duty forming fluid. It is a blend of high performance extreme pressure and lubricity additives in a fully solvent refined paraffinic mineral oil.

Application

Iloform TDN 81 is specially formulated for use in heavy duty deep drawing applications where extreme performance is required.

It is suitable for use on medium to heavy gauge steels, stainless steel, and nickel alloy steels, as well as aluminium and aluminium alloys.

Iloform TDN 81 is also recommended for use in stainless steel and alloy steel tube cold pilgering operations, where it is applied as an outer diameter roll lubricant, as well as machine gear box lubricant.

Advantages

- Contains high performance, extreme pressure additives, which provide very high resistance to temperature and pressure, and high resistance to wear. Enhanced tool and die life, cuts downtime and reduces tooling costs
- Provides a homogenous and tenacious lubricating film. Maintains excellent performance in high throughput, or multi stage operations. Consistent, high surface quality
- Flexibility. Suitable for use on a wide range of applications and materials. Allows potential for product rationalisation.
- Low odour and light colour. Excellent operator acceptance.

Typical Characteristics

Description	Test Method	Unit	Value
Appearance	Visual	-	Clear amber liquid
Density @ 15 °C	ASTM D4052 / ISO 12185	g/ml	1.18
Kinematic Viscosity @ 40 °C	ASTM D445 / ISO 3104	mm ² /s	140

Subject to usual manufacturing tolerances.

User Advice

Iloform TDN 81 can be cleaned using aqueous alkaline or solvent cleaners.

Additional Information

Additives	Ester	Active Sulphur	Inactive Sulphur	Phosphorous	Chlorine	Other
	ü					ü

Storage

To avoid product deterioration always keep the container/drum tightly sealed. Store the product in a cool, dry place away from direct sunlight. Prevent exposure to frost and avoid water ingress. For optimum product stability, it is preferable to store the product indoors between 5°C and 45 °C / 41°F and 113°F.

For more details, please refer the product safety data sheet.

Iloform™ TDN 81

26 Apr 2021

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol (UK) Limited, PO BOX 352, Chertsey Road, Sunbury On Thames, Middlesex, TW16 9AW
Orders/Enquiries: 0345 9645111 Technical Enquiries: 0345 082 1719
www.castrol.com/industrial